



Mobile barcode scanner for Android OTG devices

Features

- 2D Mini Mobile barcode scanners are designed for Android OTG devices especially.
- DC9258K: Plug & Play, No need extra driver
- Lightweight, ergonomically designed for easy operation
- With application, DC92xx series make Android OTG devices become data collector economically.



Specifications :

Model Name	DC9258K
Engine	Opticon MDI-4100

Performance Characteristics

• Illumination Element	White LED
• Aiming LED	525nm (Green)
• Depth of field	(13 mil) UPC-A : 250 mm
• Best resolution	1D (CODE39): 5 mil 2D (PDF417): 6.7 mil
• Sensor	CMOS (640×480 pixels)
Scan Angle	Tilt: 360° / Pitch ±65° / Skew ±65°
• Interface	Micro USB (USB_HID ,USB Serial <by request>)
• Print contrast	≥ 20%
• Symbologies	1D: UPC-A, UPC-A Add-on, UPC-E, UPC-E Add-on, EAN-13, EAN-13 Add-on, EAN-8, EAN-8 Add-on, JAN-8, JAN-13, Code 39, Tri-Optic, Codabar (NW-7), Industrial 2 of 5, Interleaved 2 of 5, S-Code, Code 128, Code 93, IATA, MSI/Plessey, UK/Plessey, Telepen, Code 11, Matrix 2 of 5, Chinese Post Matrix 2 of 5, Korean Postal Authority code, Intelligent Mail Barcode, POSTNET, JPN (Customer Barcode), GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Composite GS1 DataBar, Composite GS1-128, Composite EAN, Composite UPC 2D: PDF417, MicroPDF417, Codablock F, QR Code, MicroQR Code, Data Matrix (ECC 000-140 / ECC 200), Aztec Code, Aztec Runes, Chinese-sensible code, Maxi Code

Electrical Characteristics

• Input voltage	Smart Phone / Tablet Power
• Current - operating	390 mA

Physical Characteristics

• Dimension (L * W * H)	43 X 40 X 16 mm
• Color of housing	Black
• Weight	20 g

Environment

• Temperature-operation	0°C to 50°C
• Temperature-storage	-10°C to 60°C
• Humidity-operation	5% to 95% relative humidity, non-condensing

Decode Zone (DOF is measured at the office under 600 lux and by Standard barcode. There are +/- 10 mm Torrence. DOF may be also impacted by barcode quality and environmental conditions.)

• 10 mil Code 39	65 ~ 210mm
• 13 mil UPC-A	65 ~ 250mm
• 6.7 mil PDF417	60 ~ 135mm
• 10 mil PDF417	55 ~ 185mm
• 6.7 mil QR Code	75 ~ 95mm
• 15 mil QR Code	30 ~ 215mm
• 10 mil Data Matrix	60 ~ 150mm
• 7.9 mil Code 128	80 ~ 165mm

Product specification is subject to change without notice.

RIOTEC CO., LTD.

8F., 196-2, DaTong Rd., Sec. 3, Xizhi Dist., New Taipei City 221, Taiwan

TEL : +886-2-8647-1828

FAX : +886-2-8647-1800

E-mail : sales@riotec.com.tw

Web : www.riotec.com.tw